


Flexi Neon: DN0410 Series

【Features】

- **Flexible and Durable:** Provides even light output.
- **Resistant to Acid, Alkali, Corrosive Gases and UV**
- **Waterproof:** Made with environmentally friendly silicone.
- **Certified Compliance:** cULus, ROHS, and UKCA
- **High Luminous Efficiency:** Meets LM80 requirements.
- **Operating/Storage Temperature:** -25°C to 55°C (Operating), 0°C to 60°C (Storage).
- **Application:** Indoor lighting.



【Light Distribution】



AVERAGE BEAM ANGLE(50%):110.92°

Note: The above data is based on 24V monochrome 4000K color temperature.

Flux out:188.8lm

Height	Eavg	Emax	Angle	Diameter
1m	27.34,92.36lx	290.37cm		
2m	6.835,23.09lx	580.74cm		
3m	3.038,10.26lx	871.11cm		
4m	1.709,5.773lx	1161.48cm		
5m	1.094,3.695lx	1451.85cm		
6m	0.7595,2.566lx	1742.22cm		
7m	0.5580,1.885lx	2032.59cm		
8m	0.4272,1.443lx	2322.96cm		
9m	0.3375,1.140lx	2613.33cm		
10m	0.2734,0.923lx	2903.70cm		

Height Eavg,Emax Angle:110.88° Diameter

Effective average illuminance

Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

【Parameters】

SKU#	CCT/ Color Tone	CRI	Rated Working Voltage	Rated Power	Lumens	Length	Weight	QTY/ Box
LS-DN0306V12W7L5-WW	3000K	>90	12 V	7.2 W/m 2.19 W/ft	240 LM/M (73LM/ft)	5 Meter (16.4ft)	0.35 Kg/pcs 14 Kg/Box	40 Pcs/Box
LS-DN0306V12W7L5-DW	4000K				270 LM/M (82 LM/ft)			

【Notes】

